

Product Review

Awake

Carpet Tiles

04/24

pg 1/4



Product Review

Awake

Carpet Tiles



04/24

pg 2/4

Product class

Class 1 - Batch or mass-produced products

Product name

Awake Carpet Tiles

Product description and its intended use

500mm x 500mm x 6mm high carpet tile made with a multi-level loop construction consisting of 100% solution dyed nylon 6 fibre bonded to a recycled EcoBack backing system. Stocked in a range of 8 colours.

Product identifier (if applicable)

Awake Carpet Tile, colour #5101, #5201, #5202, #5301, #5401, #5901, #5902 and #5903.

Place Manufactured (New Zealand or Overseas)

Overseas, manufactured in China

Relevant Building Code clauses

B2 Durability	Performance clause B2.3.1 c) 5 years
C3 Fire Affecting Area beyond the source	Performance clause C3.4 b) - does not apply to detached dwellings, within household units in multi-unit dwellings or outbuildings and ancillary buildings.
D1 Access Routes	Performance clause D1.3.3 d)
F2 Hazardous Building Materials	Performance clause F2.3.1
G6 Airborne and Impact Sound	Performance clause G6.3.1 and G6.3.2
H1 Energy Efficiency	Functional requirement clause H1.2a) - does not apply to assembly service buildings, industrial buildings, out-buildings or ancillary buildings. Contributes to performance clause H1.2.1 (Floor coverings only contribute to the Construction R-value of Floors when using the modelling method in accordance with NZBC H1/VM1 & VM2)

Advance Flooring Systems Ltd

sales@advanceflooring.co.nz

www.advanceflooring.co.nz

Call **0508 238 262**


Advance
FLOORING SYSTEMS

Product Review

Awake Carpet Tiles



04/24

pg 3/4

Statement of how the building product is expected to contribute to compliance

B2 Durability - B2.3.1 c)

- Awake carpet tile has a durability beyond 5 years, based on NZBC B2/VM1 clause 1.1 In-service history.
- Durability supported by a 15 year product warranty for wear resistance, delamination and dimensional stability, a lifetime warranty for stain, soil and anti-static and a 15 year caster chair limited warranty.

C3 Fire Affecting Area Beyond the Source - C3.4 b)

- Awake Carpet Tile has been tested to BS EN ISO 9239.1 - 2002 and achieves a CHF (Critical Heat Flux) mean of 8.6kW/m². Refer to BTTG, Test Report 25/10431c-Supp/11/20, dated 11.1.2020.

D1 Access Routes - D1.3.3 d)

- Awake Carpet Tiles meets the requirements for slip resistance in accordance with NZBC D1/AS1 2.1 Slip Resistance, Table 2 Slip Resistance for walking surface. Awake Carpet Tiles are acceptable for level and sloping surfaces, wet and dry slip resistance.

F2 Hazardous Building Materials - F2.3.1

- Awake Carpet Tiles are manufactured from non-toxic materials
- Declare certified, Living Building Challenge Criteria complaint, LBC Red List Free

G6 Airborne and Impact Sound - G6.3.1 and G6.3.2

- Awake Carpet Tiles have been tested to EN ISO 354 for sound absorption, achieving a weighted sound absorption co-efficient of 0.20 and tested to EN ISO 10140-3 for impact sound insulation. Refer to CENTEXBEL Report 20.05402.01 Sound Absorption / Impact Sound Insulation, dated 19.10.2020

H1 Energy Efficiency - H1.2a) & H1.2.1

- Awake Carpet Tiles have been tested to ASTM C518-17 and achieve a thermal conductivity of 0.082 W/mK and thermal resistance of 0.082 (m².K)/W. Refer to Intertek Test Report 180921008SHF-001 dated 9.10.2018.

Advance Flooring Systems Ltd

sales@advanceflooring.co.nz

www.advanceflooring.co.nz

Call **0508 238 262**


Advance
FLOORING SYSTEMS

Product Review

Awake

Carpet Tiles



04/24

pg 4/4

Limitations on the use of the building product

- Awake carpet tiles are suitable for interior applications only.

Design requirements that would support the appropriate use of the building product

- Awake carpet tiles are suitable for use in high traffic, commercial areas.

Installation requirements

- Install in accordance with Advance Flooring, Installation Guide Advance Carpet Tiles for EcoBac and Comfort Backed / Mix-Bac Tiles.
- Ensure carpet tiles are from the same batch (batch number stated on box) as slight colour variation may occur from batch to batch.
- Ensure temperature at installation is between 10°C and 25°C at a relative air humidity of approximately 60%. Remove tiles from box and condition for 24 hours in room they will be installed.
- Lay Awake carpet tiles in brick, quarter-turn or Ashler pattern.
- Advance Flooring recommend the full stick installation method using Advance Flooring approved adhesives only.

Maintenance requirements

- Maintenance to be in accordance with Advance Flooring, Maintenance Guide Advance Carpet Tiles.
- Regular maintenance is required to ensure optimal performance and appearance.
- Do not use any cleaner with a pH of 10 or higher.
- Periodic cleaning by a certified carpet care professional using the standard hot water extraction method (60°) is recommended to refresh carpet appearance.

Building Act 2004 section 26 compliance

- Yes/No

Advance Flooring Systems Ltd

sales@advanceflooring.co.nz

www.advanceflooring.co.nz

Call **0508 238 262**