

Technical data sheet  
Technical data

**FINETT DIMENSION**

Wear layer	100 % polyamide <b>dorix</b> (mainly produced with renewable materials)														
Back	Textile backing (non-woven fabric)														
Emission tested acc. to TÜV PROFiCERT   acc. to CRI-principles	70 710 6625-1 (PREMIUM)   GREEN LABEL PLUS GLP100090														
Health safety Environmental label RAL-UZ 128	BLUE ANGEL Contract No. 30258														
DGNB criterion ENV 1.2	Quality Level 4 (QL 4)														
REACH regulation No. 1907/2006 article 33	does not contain any substances mentioned in the SVHC list														
Total weight ISO 8543	1300 g/m <sup>2</sup>														
Fibre weight	520 g/m <sup>2</sup>														
Wear layer weight EN 984	500 g/m <sup>2</sup>														
Total thickness ISO 1765	5,7 mm														
Dimensions	<b>Modules</b> Tile 50 x 50 cm   Plank 25 x 100 cm   4 m <sup>2</sup> /carton <b>Rolls</b> Roll width 200 cm   Roll length 25-35 m   no cut lengths possible														
Level of use EN 1307	class 33   heavy duty														
Colour fastness to light ISO 105-B02	7														
Fire rating EN 13501-1	B <sub>fl</sub> -s1														
Slipperiness EN 13893	DS (> 0,30)														
Thermal resistance ISO 8302	0,09 m <sup>2</sup> K/W suitable for underfloor heating														
Impact sound insulation ISO 10140	21 dB														
Level of sound absorption ISO 354	<table border="1"> <thead> <tr> <th>Freq. Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td><math>\alpha_s</math></td> <td>0,03</td> <td>0,03</td> <td>0,07</td> <td>0,14</td> <td>0,36</td> <td>0,53</td> </tr> </tbody> </table>	Freq. Hz	125	250	500	1000	2000	4000	$\alpha_s$	0,03	0,03	0,07	0,14	0,36	0,53
Freq. Hz	125	250	500	1000	2000	4000									
$\alpha_s$	0,03	0,03	0,07	0,14	0,36	0,53									
Anti-static ISO 6356	≤ 2,0 kV														
Special colours	> 1000 m <sup>2</sup>														
Installation DIN 18365	Removable full-surface installation with a suitable tackifier or dry adhesive. For further details please consult our installation instructions for modules and removable rolls.														



We always recommend to order larger samples. Subject to product improvements and usual colour deviations, also possible between tiles and rolls. Please also consult our installation and cleaning and maintenance instructions.

Traditional needed carpets consist of a mixture of coloured coarse fibers, which give the finished product the typical mottled look. The range of FINDEISEN also includes numerous plain colours in coarse and fine fiber optics. This results in particularly elegant surface textures with a partially felt-like appearance and a soft feel.

As with other materials, the same applies to needed carpets: covered and mottled colours hide possible stains better than bright and colourful uni shades. By choosing less sensitive colour combinations, the necessary cleaning intervals\* can be extended accordingly.

FINETT needed carpets are manufactured with utmost care and according to the latest state of the art in Ettlingen/Germany. Minor optical irregularities in the appearance of the product (for example non-matching fibers) as well as colour deviations in the sense of chapter 2.8 of the current commentary on DIN 18365 can not always be avoided due to the production process and are not a defect\*\*.

\* See also our cleaning and care instructions or the current commentary to DIN 18365: "Precondition for the suitability of the floor covering is a cleaning and care (value retention) tailored to the load, sufficient clean-up zones and the usage-relevant consideration of the colour scheme."

\*\* The obligations of the processor according to § 377 HGB remain unaffected.

